

INTRODUCING

**THE LATEST AND THE BEST !
WARM STREAM
AUTOMATIC GAS-FIRED WATER HEATER**

IDEAL FOR:
HOMES
HOTELS
HOSTELS
DAIRIES
HOSPITALS
INDUSTRIES
ETC



- HIGHLIGHTS :**
- Fully Automatic-Simple,robust construction
 - Designed for highest operational safety
 - External user-friendly + easy to maintain
 - energy - efficiency at Its best
 - Absolutely economical - cheaper than electricity

WHAT MORE CAN ONE ASK FOR !

SALIENT FEATURES :

1. Specially selected energy efficient thermal insulation significantly minimises losses.
2. Highly sensitive, quick-acting thermostat starts heating water quickly.
3. The flue baffle maximises heat absorption in the Flue Tube; by minimising air movement in the heater. During standby periods it further reduces heat loss up the flue (Smoke tube)
4. Fully automatic control shuts off the gas, once the pilot burner is extinguished either by operator or by accident.
5. Pilot burner ignites main burner once water temperature falls below pre-set level and shuts it off, as soon as the desired temperature is reached.
6. Relief, against pressure build-up through inlet cold water to overhead tank, for 100% safety.
7. Built-in gas pressure regulator ensures uniform gas flow, under all conditions.
8. Imported energy saving gas controls and cut-off mechanisms ensure absolute safety.
9. Three convenient thermostal settings at your finger tips (warm, Hot and very Hot).
10. Accordingly, you get water at the pre-set temperature throughout the 24 hrs a day. No need to fire or extinguish the burner.
11. Simple robust construction using heavy gauge steel tanks for longer life.
12. Hand-hole clean-out door makes internal cleaning very simple and easy.
13. The size of water connections provided ensures full-flow delivery to the fixture.
14. Long-dip tube introduces cold water near bottom of the tank, increasing amount of hot water available for withdrawal at top.
15. No need of any hazardous electrical controls.

Comes in choice of three convenient models :-

MODEL	RECOMMENDATION FOR CONNECTIONS				DIA M.M.	HEIGHT M.M.
	NOS. OF 1/2" Ø HOT WATER CONN.	Number OF PERSONS	COLD WATER INLET Ø	HOT WATER OUTLET Ø		
50 Letter.	1	5 to 8	1"	1"	350	1000
100 letter	2	9 to 15	1"	1"	410	1250
150 Letter	4	16 to 25	1"	1"	410	1800



ISO 9002 CERTIFIED

MANUFACTURED BY



WARM STREAM

HEAT TRANSFER PEOPLE

ANAND SOJITRA ROAD, P.O. BOX-22, VALLABH VIDYANAGAR, DIST.:ANAND.GUJARAT 388 001, INDIA.

PHONE : (02692) 31316, 32309 • FAX : (02692) 364778

SURAT OFFICE : 261-476326

E-mail : warm.stream@gnahd.global.net.in

Web site : 1) www.warmstream.co.in

2) www.warmstream.net